



BELL 1 GP-PRO XTREME

Product Description:

Bell 1 GP-PRO Xtreme Fully Synthetic motorcycle oil is specifically developed for the stringent lubricating requirements of the more and more sophisticated modern 4-stroke motorcycle engines especially those used for racing. By adopting a specially selected synthetic base, Bell 1 GP-PRO Xtreme Fully Synthetic motorcycle oil differentiates itself from the conventional 4T oils which are simply adapted from Passenger car motor oil (PCMO).

Bell 1 GP-PRO Xtreme Fully Synthetic motorcycle oil is specially formulated to take into account the unique transmission requirement and consequences of the much higher engine temperature of a modern 4T motorcycle. Reinforced with its exclusive synthetic content, Bell 1 GP-PRO Xtreme Fully Synthetic motorcycle oil is ideal to be used in a compacted, high speed and high temperature engine typically found in today's modern 4 stroke motorcycles and certainly outperforms other conventional 4T oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

Applications / Benefits:

- ▣ Strong anti-oxidation that extends engine and oil life.
- ▣ Provides correct friction properties required uniquely by the 4T motorcycle.
- ▣ Retards harmful deposit formation on vital engine parts.
- ▣ Protects against rust and corrosion.

Typical Characteristics:

Test Description	Method	10W-40	5W-50
SAE Viscosity Grade	SAE J 300	10W-40	5W-50
Specific Gravity @ 15 °C	ASTM D 4052	0.858	0.857
Flash Point, °C	ASTM D 92	226	222
Pour Point, °C	ASTM D 97	-36	-39
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	96.7	119.3
cSt @ 100°C	ASTM D 445	14.8	18.5
Viscosity Index	ASTM D 2270	160	174
TBN, mgKOH/g	ASTM D 2896	7.5	7.5
Color	ASTM D 1500	<3.0	<3.0
CCS, cP	ASTM D 5293	5623	5760
HTHS, cP	ASTM D 5481	3.6	3.9

Suggested for the following uses:

- API SN
- JASO MA2

Furnishing the information contained herein does not constitute a representation by BELL1 that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of BELL1 or any third party. BELL1 assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. BELL1 warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS OR IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.