



BELL1 DX-H

Product Description:

BELL1 DX-H is formulated using a robust additive package and hydro-treated base oil to deliver real performance in today's heavy-duty diesel engines, especially those fitted with modern features like Super-charger, Turbo-charger and multi-valves drive trains.

BELL1 DX-H is a proven choice with the transportation industry in Asian region. It minimizes high temperature carbon deposits, which is by far the most concerned issue for today's heavily loaded modern diesel engines. The reduced carbon build-up means less rings wear and cylinder bore polishing resulting in much reduced diesel consumption, less ring breakage and piston skirt scuffing. Its high ability to neutralize acidic by-products from the diesel combustion ensures minimum corrosion of the engine parts throughout the lengthy oil drain interval.

Applications / Benefits:

- Minimizes oil consumption.
- Protects against ring and cylinder wear.
- Keeps piston clean.
- Neutralizes acids from high sulfur fuel.
- Maintains efficient fuel consumption.

Typical Characteristics:

Test Description	Method	15W40*	15W50	20W50
SAE 粘度等级	SAE J 300			
Specific Gravity @ 15 °C	ASTM D 4052	0.877	0.881	0.883
Flash Point, °C	ASTM D 92	228	228	244
Pour Point, °C	ASTM D 97	-27	-27	-21
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	113.7	142.2	177.7
cSt @ 100°C	ASTM D 445	14.8	18.1	19.8
Viscosity Index	ASTM D 2270	134	142	129
TBN, mgKOH/g	ASTM D 2896	10.0	10.0	10.0
Color	ASTM D 1500	≤ 2.5	≤ 2.5	≤ 2.5

Specifications, Approvals & Recommendations:

- API CH4/SJ
- Cummins CES20076
- ACEA E5-02
- Mercedes-Benz 228.1 / 228.3
- MAN M3275
- MAN 270 / 271
- Mack Cat 1 / Cat 2
- VOLVO VDS-2

* Please note performance is SAE grade specified.

Furnishing the information contained herein does not constitute a representation by BELL1 that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of BELL1 or any third party. BELL1 assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. BELL1 warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.