



BELL 1 B-MAX PLUS SPORT 4T LPG

Product Description:

BELL 1 B-Max Plus Sport 4T LPG is a multi-function lubricant designed specially for vehicles burning gas as the fuel. It contains a balanced blend of select high performance, high viscosity index hydrocracked base stocks and a special proprietary anti-oxidation additive package that ensure it works perfectly in the usually red hot gas engine because of burning fuel gas.

Applications / Benefits:

- ▣ Reduces engine wear and extends engine life.
- ▣ Protects engine under high temperature operating conditions.
- ▣ Retards harmful deposit formation on vital engine parts.
- ▣ Protects against rust and corrosion.

Typical Characteristics:

| Test Description | Method | |
|---------------------------------|-------------|---------------|
| SAE Viscosity Grade | SAE J 300 | 20W-50 |
| Specific Gravity @ 15 °C | ASTM D 4052 | 0.875 |
| Flash Point, °C | ASTM D 92 | 232 |
| Pour Point, °C | ASTM D 97 | -18 |
| Kinematic Viscosity, cSt @ 40°C | ASTM D 445 | 192.2 |
| cSt @ 100°C | ASTM D 445 | 20.5 |
| Viscosity Index | ASTM D 2270 | 124 |
| TBN, mgKOH/g | ASTM D 2896 | 6.1 |
| Color | ASTM D 1500 | 2.5 |

Suggested for the following uses:

- API SL
- JASO MA2